

Windows 主机如何设置伪静态

IIS7.5 伪静态规则只要将规则保存在 web.config 然后上传到主机的根目录下面即可

案例：discuz(DZ 2.5)开启伪静态教程

1. 首先登录 discuz 后台，点击 全局 选择 SEO 设置 勾选 可用下的选项



2. 点击 查看当前的 Rewrite 规则 URL

与资源消耗有关(提高效率、或降低效率)，建议依据自身服务器情况进行调整。



3. 复制伪静态代码

IIS7 Web Server(独立主机用户)

```
<rewrite>
  <rules>
    <rule name="portal_topic">
      <match url="(.*?)topic-(.+).html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/portal.php?mod=topic&topic={R:2}&{R:3}" />
    </rule>
    <rule name="portal_article">
      <match url="(.*?)article-[0-9+]-[0-9+].html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/portal.php?mod=view&aid={R:2}&page={R:3}&{R:4}" />
    </rule>
    <rule name="forum_forumdisplay">
      <match url="(.*?)forum-(\w+)-[0-9+].html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/forum.php?mod=forumdisplay&fid={R:2}&page={R:3}&{R:4}" />
    </rule>
    <rule name="forum_viewthread">
      <match url="(.*?)thread-[0-9+]-[0-9+]-[0-9+].html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/forum.php?mod=viewthread&tid={R:2}&extra=page%3D[R:4]&page={R:3}&{R:5}" />
    </rule>
    <rule name="group_group">
      <match url="(.*?)group-[0-9+]-[0-9+].html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/forum.php?mod=group&fid={R:2}&page={R:3}&{R:4}" />
    </rule>
    <rule name="home_space">
      <match url="(.*?)space-(username|uid)-(.+).html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/home.php?mod=space&{R:2}={R:3}&{R:4}" />
    </rule>
    <rule name="home_blog">
      <match url="(.*?)blog-[0-9+]-[0-9+].html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/home.php?mod=space&uid={R:2}&do=blog&id={R:3}&{R:4}" />
    </rule>
    <rule name="forum_archiver">
      <match url="(.*?)({fid|tid}-[0-9+]).html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/index.php?action={R:2}&value={R:3}&{R:4}" />
    </rule>
    <rule name="plugin">
      <match url="(.*?)([a-z]+[a-z0-9_]*-[a-z0-9_]+).html\?(.*)$" />
      <action type="Rewrite" url="{R:1}/plugin.php?id={R:2}:{R:3}&{R:4}" />
    </rule>
  </rules>
</rewrite>
```

4 在网站根目录下创建一个 web.config 文件，然后将代码粘贴进去。

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<configuration>
```

```
  <system.webServer>
```

```
    <rewrite>
```

```
      <rules>
```

```
        <rule name="portal_topic">
```

```
          <match url="^(.*)*topic-(.+).html\?(.*)$" />
```

```
          <action type="Rewrite"
```

```
url="{R:1}/portal.php?mod=topic&topic={R:2}&{R:3}" />
```

```
        </rule>
```

```
        <rule name="portal_article">
```

```
          <match url="^(.*)*article-[0-9+]-[0-9+].html\?(.*)$" />
```

```
          <action type="Rewrite"
```

```
url="{R:1}/portal.php?mod=view&aid={R:2}&page={R:3}&{R:4}" />
```

```
        </rule>
```

```
        <rule name="forum_forumdisplay">
```

```
          <match url="^(.*)*forum-(\w+)-[0-9+].html\?(.*)$" />
```

```
          <action type="Rewrite"
```

```
url="{R:1}/forum.php?mod=forumdisplay&fid={R:2}&page={R:3}&{R:4}" />
```

```
        </rule>
```

```
        <rule name="forum_viewthread">
```

```
          <match url="^(.*)*thread-[0-9+]-[0-9+]-[0-9+].html\?(.*)$" />
```

```
          <action type="Rewrite"
```

```

url="{R:1}/forum.php\?mod=viewthread&tid={R:2}&extra=page%3D{R:4}&page
={R:3}&{R:5}" />
    </rule>
    <rule name="group_group">
        <match url="^(.*)*group-([0-9]+)-([0-9]+).html\?*(.*)$" />
        <action
                                                    type="Rewrite"
url="{R:1}/forum.php\?mod=group&fid={R:2}&page={R:3}&{R:4}" />
    </rule>
    <rule name="home_space">
        <match url="^(.*)*space-(username|uid)-(.+).html\?*(.*)$" />
        <action
                                                    type="Rewrite"
url="{R:1}/home.php\?mod=space&{R:2}={R:3}&{R:4}" />
    </rule>
    <rule name="home_blog">
        <match url="^(.*)*blog-([0-9]+)-([0-9]+).html\?*(.*)$" />
        <action
                                                    type="Rewrite"
url="{R:1}/home.php\?mod=space&uid={R:2}&do=blog&id={R:3}&{R:4}"
/>
    </rule>
    <rule name="forum_archiver">
        <match url="^(.*)*(fid|tid)-([0-9]+).html\?*(.*)$" />
        <action
                                                    type="Rewrite"
url="{R:1}/index.php\?action={R:2}&value={R:3}&{R:4}" />
    </rule>
</rules>
</rewrite>

<defaultDocument>
    <files>
        <clear />
        <add value="index.asp" />
        <add value="default.html" />
        <add value="Default.htm" />
        <add value="Default.asp" />
        <add value="index.htm" />
        <add value="index.html" />
        <add value="iisstart.htm" />
        <add value="default.aspx" />
        <add value="index.php" />
    </files>
</defaultDocument>
</system.webServer>
</configuration>

```